



#### **EPOXY RESIDUE REMOVER**

Product formulated for the removal and quick clean-up of epoxy grout haze and stains, residues, stubborn adhesive and epoxy-based coatings from vertical and horizontal surfaces. Ideal for post installation clean ups and for excessive epoxy residues.



#### **CHEMICAL PROPERTIES**

ASPECT: Gel
COLOUR: Colourless
ODOUR: Characteristic
SOLUBILITY: Soluble in water
PH: 7,00±0,50

#### **INDICATIVE COVERAGE FOR LITRE**

Approximately 15m<sup>2</sup>

Product coverage may vary depending on type and porosity of material where used

PACKAGING		
Code	Content	Pc./Carton
P034RMX10L	1 lt	6
P034RMX50L	5 lt	4

www.bellinzoni.com MADE IN ITALY



ormation:

#### ATTENTION:

#### Carefully read the recommendations printed on the label. Always test before use. Do not dispose of the container in the environment after use, follow the disposal information indicated on the label. Keep out of reach of children. The product has anti-stain properties but does not protect surfaces from acids. Check the actual resistance of the material to the product on a hidden portion of the surface to be treated. When using the product, use suitable PPE and consult the safety data sheet.

## **SURFACES**

Tiles, glazed ceramics, gres porcelain, glass mosaic, natural stone, clinker, terracotta and quartz, Porphyry and Sandstones.

# **FEATURES**

Specific cleaner indicated for dissolving and breaking down fresh and stubborn (hard, old,) excessive epoxy residues. Special slow drying formulation allows product to be used on used indoor, outdoor, hot damp and humid areas and on sun exposed surfaces. Gel formula. Safe and easy to use on vertical surfaces.

## **HOW TO USE**

Apply a thick amount of product using a soft bristle brush directly over stain or residues to be removed. Allow a contact time of 30 minutes for fresh stains, smudges and haze. For older, hardened and stubborn stains allow for a contact time of 40 minutes. Allow product to dissolve residues before removing substance using a clean cotton cloth or sponge and water. Rinse surface and repeat operation if necessary. For large areas, use the floor scrubbing machine.

### **ADVANTAGES**

Special neutral pH, low VOC, low odour, non-flammable formulation ideal for use on any surfaces and areas. Due to its specific gel like formulation and active ingredients allows product to work rapidly directly on the stain, saving time without wasting product dripping. Can be applied to warm and sun exposed surfaces.

## **ADVICE**

B-REMOXY can be also used for the clean up of tools and machinery with stubborn epoxy residues. On vertical surfaces, apply product using a large soft bristle brush for complete coverage.