

Technical Data Sheet

Page 1 of 1

- Properties:** AKEMI® Colouring Concentrates liquid / Colouring Pastes are concentrates in different colour shades. The products are characterized by the following properties:
- easy colouring of epoxy-based adhesives
 - the liquid consistency (of concentrates) makes it easier to mix with liquid products
 - matching the colour of the adhesive to many common stone colours
 - balanced pigment concentration, thus easy adjustment of different colour shades and high coverage
 - extremely UV- and light-resistant pigments, i.e. no fading
 - no deterioration of the properties of the coloured adhesives
- Application Area:** AKEMI® Colouring Concentrates liquid / Colouring Pastes are used for colouring AKEPOX® fillers and adhesives. Thus, the colour of the adhesive can be adjusted to the respective stone colour.
- Instructions for Use:**
1. Add maximum 5% of AKEMI® Colouring Concentrate liquid / Colouring Paste to the adhesive to be coloured, depending on the colour of the concentrate and the stone.
 2. Mix well until a homogenous shade of colour is achieved.
- Special Notes:**
- For professional use only.
 - Use afin® Liquid Glove to protect your hands.
 - Hardener to be added after the colour had been adjusted.
 - For proper waste disposal, the container must be completely emptied.
 - Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.
- Technical Data:** Colours: red, redbrown, white, black, ochre, green, brown, blue
Colouring Concentrates: additionally beige, grey
- Storage:** If stored in dry and cool condition (5-25°C/41-77°F) in its closed original container at least 3 years from production.
- Health & Safety:** Read Safety Data Sheet before handling or using this product.
- Important Notice:** The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample piece.