# **Mira Dust**

# Sealants Company www.miraclesealants.com

# **Polishing Powder For**

| <ul><li>Marble</li><li>Limestone</li></ul>              | <ul><li>Terrazzo</li><li>Other Natural Stone</li></ul> | <ul><li>Travertine</li><li>Furniture</li></ul>                      |  |
|---|--|---|--|
| <b>Special Features</b>                                 |  |   |  |
| <ul> <li>No Oxalic Acid</li> <li>Safe to Use</li> </ul> | <ul> <li>Easy to Use</li> <li>Fast Acting</li> </ul>   | <ul> <li>Interior &amp; Exterior</li> <li>Cost Effective</li> </ul> |  |

# PRODUCT DESCRIPTION

KEEP OUT OF REACH OF CHILDREN. Mira Dust polishing powder is a unique blend designed to enhance the natural shine of natural stone and terrazzo. Mira Dust will remove light scratches, water rings and acid etch marks. Mira Dust is an effective means of maintaining the factory finish of marble, travertine, limestone, terrazzo and other natural stone surfaces. Unlike recrystallization or vitrification, Mira Dust does not change the surface composition of the stone. Mira Dust is an easy to use polishing process that has been used in stone factories and in the field for decades. Mira Dust is great for ongoing maintenance, as well as the final polishing step in any stone restoration procedure. Heavy scratches and etch marks may need to be honed with Mira Hone or with the Pyramid Diamond Abrasive System.

#### **Sample Testing**

Due to the differences of each material, several inconspicuous test patches should be completed to assure maximum performance. **User must determine suitability of the product for their intended use.** 

# **Special Precaution & Protection**

Always protect neighboring surfaces including wood, carpet, metal, landscaping and other non masonry surfaces. **Mira Dust** should not be left on the surface for any length of time without constant buffing action. If buffing is stopped **Mira Dust** must be immediately picked up to avoid burning. Place the floor or hand machine on a plastic or teflon sheet when not in use. **Mira Dust** is not recommended for granite or synthetic surfaces. **Mira Dust** can be run through a sifter for a more consistent powder.

# APPLICATION INSTRUCTIONS

# Read entire label and SDS/PDS before using.

All previous applied sealers, coatings and/or waxes must be removed using **Mira Strip** or **Finish Sealer Stripper** as directed.

Using a **Marble Master 1000** (175 rpm, 150 lbs.) floor machine equipped with a white polishing pad or a tampico brush will provide optimum results. Wet a small area (2 - 4 sf) with clean water. Sprinkle **Mira Dust** on the area and buff making slow, even passes side to side. Add water or **Mira Dust** as needed to maintain a watery/milky slurry. DO NOT ALLOW **MIRA DUST** SLURRY TO DRY ON THE SURFACE. Buff the stone for 1 - 2 minutes or until desired polish is achieved. Additional buffing with **Mira Dust** may be used to increase polish. A floor squeegee may be used to move the solution to the next small area to be polished. Be careful not to buff too long in any given area as this may create a burn. After polishing, rinse the stone thoroughly with a **Tile & Stone Cleaner** solution (20 - 1). Agitate with a soft brush and remove using a wet vacuum. This procedure is essential for neutralization of the polished surface.

**Counters:** Use a hand machine (600 - 800 rpm) equipped with a white pad or tampico brush and use in the same manner as with floors.

**Wall:** Wet the small area to be worked and sprinkle the **Mira Dust** directly onto the polishing pad or brush. Buff the walls in small sections. Be careful to protect neighboring areas from dripping of the **Mira Dust** solution.

**Small Areas: Mira Dust** can be worked by hand for very small areas or trouble spots. Follow the same procedure as above, buffing with a small white pad and using rubber gloves. This method can effectively remove many light scratches, water rings and etch marks while restoring desired luster to those very small and hard to reach areas.

Heavy Duty Cleaning: Use Phosphoric Acid Cleaner , HDAC or Liquid Poultice as directed.

Light Cleaning: Use Tile & Stone Cleaner or Counter Kleen as directed.

# Water, Stain & Slip Protection

Application of **Miracle Penetrating Sealer/Impregnator** will reduce penetration of all staining materials and make the surface less slippery.

# Coverage

Coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface and application methods. Used as directed, **Mira Dust** will do approximately 150 - 300 square feet (14 - 27 sq. meters) per pound.

# MAINTENANCE

For ongoing maintenance instructions please refer to **Miracle Sealants Care Guide.** Refer to the **Miracle Sealants Product Recommendation Chart** for specific product recommendations.

# Storage

Store **Mira Dust** in the original upright container properly sealed and unmixed. Stored at 77° F (25° C), **Mira Dust** will have a shelf life of 12 months. Do not allow to freeze.

# **Technical Support**

For additional technical support, contact Miracle Sealants Company at 1-800-350-1901 or 626-443-6433 ext. 3013

# Office Hours

Monday - Friday from 8:30 am - 5:00 pm PT. 1-626-443-6433 or 1-800-350-1901 • Fax: 1-626-443-1435 website: www.miraclesealants.com

# **Product Damaged During Transportation**

If product is damaged during transportation contact Info Trac @ 1-800-535-5053

#### **Additional Products**

Miracle Sealants Company offers a complete line of water & stain repellents, sealers, cleaner, polishing compounds, diamond abrasives, machinery and accessories for the tile, stone, concrete, metal, fabric and carpet professional or do-it yourself specialist.

#### Caution

Use in a well ventilated area. This product contains a mild corrosive and must be used only as directed. **KEEP OUT OF REACH OF CHILDREN**. Avoid contact with food or beverages and risk of accidental ingestion. Do not transfer to other bottles or containers. Protect skin and eyes. If exposed flush with water. Chemical resistant gloves should be worn at all times. Keep small children and pets out of area until product or surface has thoroughly dried. **Refer to the MSDS for additional information**.

# Warranty

Instructions are a condensed guide and should not be considered complete. In the event of failure, the only obligation of Miracle Sealants Company shall be to replace such products proven to be defective. **Before** using, user shall determine the suitability of the product for their intended use. User assumes all risks and liability whatsoever in connection therein. Neither seller nor manufacturer shall be liable for any injury or inability to use this product.